

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)


PCT

(10) International Publication Number  
**WO 2004/028640 A1**

- (51) International Patent Classification<sup>7</sup>: **A62B 18/10**
- (21) International Application Number:  
PCT/GB2003/004207
- (22) International Filing Date:  
29 September 2003 (29.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0222497.0 27 September 2002 (27.09.2002) GB
- (71) Applicant (for all designated States except US): **THE SECRETARY OF STATE FOR DEFENCE** [GB/GB]; DSTL, Porton Down, Salisbury, Wiltshire SP4 0JQ (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **RICHARDSON, Grant, Stuart** [GB/GB]; DSTL, Porton Down, Salisbury, Wiltshire SP4 0JQ (GB). **ROWBATHAM, Alex, Scott** [GB/GB]; DSTL, Porton Down, Salisbury, Wiltshire SP4 0JQ (GB). **WILLIAMS, Graham, Howell** [GB/GB]; DSTL, Porton Down, Salisbury, Wiltshire SP4 0JQ (GB).
- (74) Agent: **BECKHAM, Robert, William**; D/IPR Formalities Section, Poplar 2, MOD Abbey Wood #2218, Bristol BS34 8JH (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: RESPIRATOR



(57) Abstract: A valve assembly (20) for a respirator comprises a valve body (25) having a valve outlet portion and a valve inlet portion which together define a valve cavity (30) for a valve mechanism (24) permitting gas flow from the valve inlet portion to the valve portion member, an air purge means comprising a purge inlet, connectable to an air pressure supply means, an air purge outlet (27) and an air deflection means (28) in which the deflection means is spatially arranged relative to the valve mechanism and purge outlet so that, in use, air exiting the purge outlet and incident the air deflection means provides a curtain of air over the valve mechanism.

WO 2004/028640 A1